

JUTA UK LTD
PROJECT

JUTA GP1® SAM Typical Details



Detail is generic to application so should be used as a quide not a specific installation detail.

JUTA suggest that waterproofing membranes including JUTA GP1 SAM should be installed by suitably experienced persons. If unfamiliar with products and applications, please contact JUTA for Specialist Contractors Details.

JUTA GP1 SAM can be applied to reinforced concrete, concrete blockwork and masonry. It can also be applied to various masonry wall systems (i.e. ICF or Stepoc.) but please contact JUTA or a specialist to confirm suitability of primers and adhesive on structure.

All surfaces must be prepared with 1 coats of JUTA GP Primer before application. Please refer to JUTA SAM Installation Guide for further information

All externally applied membrane should be protected from damage prior to backfilling. This can be achieved using standard protection boards or better still, JUTA PD1700 which is a protection and drainage sheet layer which additionally creates a void between the membrane and earth to reduce the change of hydrostatic pressure onto the structure and direct any groundwater to land drain locations.

All design decisions made by others that might have an impact on the gas and waterproof design performance should be brought to the
attention of the design team and Juta UK Ltd. Final decisions and/or any recommendations should be approved by the design team and Juta UK
Ltd.

- Dimensions are not to be scaled from this drawing. All written measurements are to be checked on site by the contractor.
- All rights described in chapter IV of the copyright, design and patents act 1988 have been generally asserted.

RAWING TITLE

JUTA WP SAM (SELF ADHESIVE MEMBRANE) RC RETAINING WALL/ SLAB WITH TOE DETAIL

DRAWING NUMBER

JUTA.GP1-SAM.oo5

PD PF Scale Mar. 2020



MELTON GROVE WORKS BLACKPOOL ROAD LYTHAM FY8 5PL

Tel: 01772 754177