



CLIENT
JUTA UK LTD

PROJECT
Hydrolock Standard Details



NOTES

- Detail is generic to application so should be used as a guide not a specific installation detail.
- JUTA suggest that waterproofing membranes including JUTA Hydrolock should be installed by suitably experienced persons. If unfamiliar with products and applications, please contact JUTA for Specialist Contractors Details.
- JUTA Hydrolock should be pre-applied onto a sandblinding horizontally, and mechanically fixed to vertical shuttering prior to reinforced concrete being poured. It is possible to post apply small sections where pre-applying is not suitable but please contact JUTA or speak to the project specialist installer for further guidance.
- Please refer to JUTA Hydrolock Installation Guide for further information
- All externally applied membrane should be protected from damage prior to backfilling. This can be achieved using standard protection boards or better still, JUTA PD1700 which is a protection and drainage sheet layer which additionally creates a void between the membrane and earth to reduce the change of hydrostatic pressure onto the structure and direct any groundwater to land drain locations.
- All design decisions made by others that might have an impact on the gas and waterproof design performance should be brought to the attention of the design team and Juta UK Ltd. Final decisions and/or any recommendations should be approved by the design team and Juta UK Ltd.
- Dimensions are not to be scaled from this drawing. All written measurements are to be checked on site by the contractor.
- All rights described in chapter IV of the copyright, design and patents act 1988 have been generally asserted.

DRAWING TITLE
JUTA HYDROLOCK
HYDROLOCK STRIP KICKER JOINT DETAIL

DRAWING NUMBER
JUTA.HDL.021

DRAWN BY PD	CHECKED BY PF	SCALE Not to Scale	DATE March. 2021
----------------	------------------	-----------------------	---------------------



MELTON GROVE WORKS
BLACKPOOL ROAD
LYTHAM
FY8 5PL
Tel: 01772 754177