

DRAWING TITLE

External Retaining Wall - External Tanking

NOTES

- Detail is generic to application so should be used as a guide not a specific installation detail.

 JUTA suggest that waterproofing membranes including JUTA WP SAM should be installed by suitably experienced persons. If

 unfamiliar with products and applications, please contact JUTA for Specialist Contractors Details.

 JUTA WP SAM can be applied to reinforced concrete, concrete blockwork and masonny. It can also be applied to various masonny wall
 systems (i.e. ICF or Stepoc.) but please contact JUTA or a specialist to confirm suitability of primers and adhesive on structure.

 All surfaces must be prepared with a coats of JUTA GP Primer before application. A minimum of ahrs must be left event contact to allow the primer to become tacky to aid adhesion. Please refer to JUTA WP SAM Installation Guide for further information

 All externally applied membrane should be protected from damage prior to backfilling. This can be achieved using standard protection boards or better still, JUTA PD1700 which is a protection and drainage sheet layer which additionally creates a void between the membrane and earth to reduce the change of hydrostatic pressure onto the structure and direct any groundwater to land drain locations.

 All design decisions made by others that might have an impact on the gas and waterproof design performance should be brought to the attention of the design team and Juta UK Ltd. Final decisions and/or any recommendations should be approved by the design team and Juta UK Ltd.

 Dimensions are not to be scaled from this drawing. All written measurements are to be checked on site by the contractor.

 All rights described in chapter IV of the copyright, design and patents act 1988 have been generally asserted.

DRAWING NUMBER

TD-JUTA.WP-SAM.017

DRAWN BY CHECKED BY PD PF Not to Scale Nov 2019



MELTON GROVE WORKS BLACKPOOL ROAD LYTHAM FY8 5PL

Tel: 01772 754177